

> 2604 CENTRALIZED OFFICE SHREDDER WITH AUTOMATIC OILER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off (avoids paper jams); automatic power cut-off when shred bin is full or when cabinet door is opened; double protection against overheating; "ESM" (Energy Saving Mode) after 1 hour of inactivity | automatic start and stop controlled by photo cell | "ECC" (Electronic Capacity Control) indicator helps prevent paper jams by indicating sheet capacity levels during the shredding process | automatic oil injection insures optimal performance at all times | wide, 10 ½" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, credit cards, and CDs (strip- and cross-cut models) | super micro-cut (SMC) model meets all NSA/CSS specifications and is DOD approved | lifetime warranty on the cutting shafts (strip- and cross-cut models) | 1 year warranty on SMC cutting shafts | quiet and powerful single phase motor rated for continuous operation | sturdy "twin drive system" with dust-proof gear box housing | high quality wooden cabinet mounted on casters | convenient shred bin | 26 gallon shred volume (approximate)

Dimensions (D x W x H): $18 \frac{1}{2}$ x $22 \frac{1}{2}$ x $36 \frac{1}{2}$ inches, Shipping weight: 123 lbs.









CAPACITY INDICATOR



"ECC" (Electronic Capacity Control) indicator helps prevent paper jams by monitoring capacity levels during operation.

→ 2604 STRIP-CUT

Strip width 3/16"
Sheet capacity 27-30*
Security level 2
Feed opening 10 ¼"
Max. horsepower 1

→ 2604 CROSS-CUT

Particle size 3/16" x 1 ½"

Sheet capacity 20-22*

Security level 3

Feed opening 10 ½"

Max. horsepower 1 → 2604 CROSS-CUT

Particle size 3/32" x 5/8"
Sheet capacity 12-14*
Security level 4
Feed opening 10 ¼"
Max. horsepower 1

→ 2604 SMC HIGH SECURITY

Particle size 1/32" x 3/16"
Sheet capacity 6-8*
Security level 6
Feed opening 10 1/4"
Max. horsepower 1

* may vary due to variations in paper and power supply

All technical data is approximate and subject to change. © MBM Corporation, 9/2009.

VEVCORPORATION

3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com IDEAL. VEW CORPORATION

1675 Sismet Road, unit 4 Mississauga, Ontario L4W 4K8 800-387-2528, fax: 905-840-1114 www.ideal-mbm.com Dealer:



Printer's Parts & Equipment 60 Howden Road Scarborough, Ontario

Scarborough, Ontario Phone: 416-752-4488 Toll Free: 1-800-268-6577 www.printersparts.com